

DS-VE11D-C/HW01(C) General Purpose Server



- Designed for budget-conscious businesses
- Simple to install, manage, and deploy
- Keep your data safe

▪ Specification

Hardware Specifications	
CPU	E-2324G x 1
Hard Disk	1 TB 7.2K SATA × 2
Device Dimensions	Height: 42.8 mm(1.68 inches) Width: 482.00 mm (18.97 inches) Depth: 598.64 mm (23.56 inches) with bezel 585 mm (23.03 inches) without bezel
Memory	16 GB DDR4 DIMM
Storage Controller	H355 × 1
Power Supply	Single 450 W (bronze) power supply
Embedded Management	iDRAC9 iDRAC Direct iDRAC RESTful API with Redfish iDRAC Service Manual
Integrations and Connections	Integrations: Microsoft® System Center, VMware® vCenter™, BMC Truesight (available from BMC), Red Hat Ansible Connections: Nagios Core & Nagios XI, Micro Focus Operations Manager i (OMi), IBM Tivoli Netcool / OMNibus
I/O & Ports	NIC: 2 × 1GbE LOM Network Interface Controller (NIC) ports Front ports: 1 × USB 2.0 ; 1 x iDRAC Direct (Micro-AB USB) port Rear ports: 1 × USB 3.0, 1 × USB 2.0, 1 x VGA, 1 x serial connector, 1 x iDRAC ethernet port
Supported Operating Systems	This model is installed with Windows Server 2019 multilingual operating system.
Physical and Environmental Parameters	
Net Weight (without package)	12.2 kg (26.9 lb.)
Gross Weight (with package)	18.5 kg (40.79 lb.)

▪ Available Model

DS-VE11D-C/HW01(C)

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq